

**MARSH LANDING
VILLA II HOME OWNERS ASSOCIATION
DRIVEWAY – WALKWAY PAVER SPECIFICATION SHEET**

Driveways, front walkways and entrances may be replaced with pavers. When a driveway is replaced with pavers, the front walkway must also be replaced with pavers. Exposed gravel or crushed stone driveways or walkways are not permitted. Painting of walkways and driveways are not permitted.

The pavers must touch to provide a level and flat appearance and must have concrete edging to hold in place. All paver areas must be sealed with penetrating sealer.

The homeowner is financially responsible for the relocation of all irrigation lines and/or heads and liable for any damages. Cleanup including street and restoration of area must occur within 24 hours of project's completion and no equipment may be left overnight on the street.

COLOR: Blend of these three - Chestnut- Buff-Charcoal (Euro-Cobble #623406)
Manufacture: Tri-Circle Pavers

PATTERN: Random Running Board (Approximate 60% rectangle & 40% Square)

APPROXIMATE SIZES: (A) 6 ¼" X 6 ¼" & 9 ¼" X 6 ¼" Select _____
(Select (A) or (B)) (B) 9 ¼" X 9 ¼" & 9 ¼" X 12 ½" Select _____

PAVER THICKNESS: 2 3/8"

Contractor's contract must be attached (prices can be blacked out)

The homeowner has two weeks to complete this job from date work begins. Approval expires three months from approval date. Home owner is responsible to insure contractor has proper license and carries proper insurance.

Homeowners Name _____ Phone _____
Address _____
E mail _____

Homeowners Signature _____ DATE _____

BOARD USE ONLY:

Approved _____ Not Approved _____ Date _____
Approved _____ Not Approved _____ Date _____
Approved _____ Not Approved _____ Date _____